
Sweepers for tractors and municipal vehicles







Use Sweeper roller types

- Combination sweeper roller (standard factory setting) For over 90% of all applications
- Poly-corrugated wire sweeping roller For high levels of stubborn dirt, e.g. moss etc.
- Dirt sweeping roller Suitable for larger amounts of dirt due to
- Snow sweeping roller A special bristle arrangement with a larger the snow is optimally transported away.

Practical accessories

- Dirt collection container
 The sweepings are collected in one operation
- Rubber spray flap To reduce flying dirt particles
- Side broom For collecting dirt even in side areas, z. e.g. kerb gutters etc.
- Parking supports For longer storage in order not to damage the sweeping roller

Hydraulic Container emptying













Sweepers for small tractors

| Measurements | KM 13050 M | KM 14750 M | KM 16550 M | KM 13050 H | KM 14750 H | KM 16550 H |
|---|------------|------------|------------|------------|------------|------------|
| measurements | KM 13030 M | KM 14730 M | KM 10550 M | KW 13030 H | KM 14750 H | KM 10550 H |
| A: Working width straight; without side broom [cm] | 130 | 147 | 165 | 130 | 147 | 165 |
| B: Working width straight; with side broom [cm] | 153 | 170 | 188 | 153 | 170 | 188 |
| Working width sloping [cm] | 118 | 134 | 150 | 118 | 134 | 150 |
| C: Straight passage width; without side brushes [cm] | 142 | 159 | 177 | 142 | 159 | 177 |
| D: Straight passage width; with side brushes [cm] | 148 | 165 | 183 | 148 | 165 | 183 |
| Clearance width sloping; without SSB [cm] | 138 | 155 | 173 | 138 | 155 | 173 |
| E: Length; including SSB; without attachment frame [cm] | 137 | 137 | 137 | 137 | 137 | 137 |
| F: Length; without SSB; without attachment frame [cm] | 86 | 86 | 86 | 86 | 86 | 86 |
| G: Height; without attachment frame [cm] | 82 | 82 | 82 | 82 | 82 | 82 |
| Brush diameter [cm] | 50 | 50 | 50 | 50 | 50 | 50 |
| Swivel angle [degrees] | 24 | 24 | 24 | 24 | 24 | 24 |
| Sweeping mirror [cm] | 8-10 | 8-10 | 8-10 | 8-10 | 8-10 | 8-10 |
| Weights | | | | | | |
| Basic unit [kg] | 162 | 175 | 185 | 162 | 175 | 185 |
| Collecting container [kg] | 67 | 73 | 80 | 67 | 73 | 80 |
| Side brushes [kg] | 40 | 40 | 40 | 40 | 40 | 40 |
| Water sprinkler 100 litres ; full tanks [kg] | 126 | 126 | 126 | 126 | 126 | 126 |
| Volume | | | | | | |
| Collection tank [ltr] | 95 | 102 | 115 | 95 | 102 | 115 |
| Water sprinkler [ltr] | 100 | 100 | 100 | 100 | 100 | 100 |
| Capacity | | | | | | |
| Oil volume [ltr/min] at 180 bar | 35 | 35 | 35 | 35 | 35 | 35 |
| Tractor power [hp] | 25 | 25 | 25 | 25 | 25 | 25 |





Sweeping mirror

| KM 13050 M-ABR 50 (without attachment frame) Sweeper mechanically driven Working you have that in the full of the original combination sweeper role included : 5 Heght-adjustable wheels via spindles with threat bearing : Pendulum suspended : 2 Leight-adjustable wheels via spindles with threat bearing : Rubber spong rubps included : 1 Houding gaarking support RBR 50 required KM 14750 M-ABR 50 (without attachment frame) Sweeper mechanically driven Working width 147 cm For further description see KM 13050 M-ABR 50 KM 14550 H-ABR 50 (without attachment frame) Sweeper mechanically driven Working width 165 cm For further description see KM 13050 M-ABR 50 KM 14550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm : 1 Hydraulically driven Working width 165 cm : 2 Heght-adjustable wheels via spindles with thrust bearing 280 x 50 mm : 1 Haber sping 10 Hear 50 (without attachment frame) KM 14550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm : 1 Hydraulically driven Working width 162 cm : 2 Heght-adjustable wheels via spindles with thrust bearing 280 x 50 mm : 1 Haber sping 10 Hear 50 For further description sec KM 13050 H-ABR 50 KM 14550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm : For further description sec KM 13050 H-ABR 50 KM 14550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Wo | | Item number | Description |
|--|--|-------------|--|
| (without attachment frame) Working width 147 cm For further description see KM 13050 M-ABR 50 KM 16550 M-ABR 50 (without attachment frame) Sweeper mechanically driven Working width 165 cm For further description see KM 13050 M-ABR 50 KM 13050 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm • Hydraulically driven Urbital motor • Hydraulically driven • Supports included • Hydraulically driven • Hydraulically driven • Supports included • Hydraulically driven Working width 147 cm For further description see KM 13050 H-ABR 50 KM 16550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm For further description see KM 13050 H-ABR 50 KM 16550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm For further description see KM 13050 H-ABR 50 KM 16550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm For further description see KM 13050 H-ABR 50 Attachment frame for compact tractor sweepers When ordering, s | | | Working width 130 cm Quick change axle Combination sweeper roller included Hydraulically swivelling left and right (1 x dw required) Pendulum suspended 2 height-adjustable wheels via spindles with thrust bearing wheels 200 x 50 mm Rubber spray flaps included Including cardan shaft Including parking support |
| (without attachment frame) Working width 165 cm For further description see KM 13050 M-ABR 50 KM 13050 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm • Hydraulically driven • Hydraulically driven Usick change axle • Combination sweeper roller included • Hydraulically driven • Hydraulically driven • Usick change axle • Combination sweeper roller included • Lydrauliceleft and right switel (1 x dw required) • Pendulum suspended • Lydrauliceleft and right switel (1 x dw required) • Hydrauliceleft and right switel (1 x dw required) • Rubber spary flags • Supports included • Supports included • Supports included ABR 50 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 147 cm For further description see KM 13050 H-ABR 50 KM 16550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm For further description see KM 13050 H-ABR 50 Attachment frame for compact tractor sweepers When ordering, specify exact carrier vehicle type and attachment type. Attachment frame for dome-triangle mounting ABR 50 KD Attachment frame three-point linkage Cat I and II ABR 50 KD Attachment frame area mower (2-point) | | | Working width 147 cm |
| (without attachment frame) Working width 165 cm Hydraulically driven - Hydraulically driven Quick change axle - Combination sweeper roller included Combination sweeper roller included - Hydraulically driven - Hydraulically driven - Combination sweeper roller included - Hydraulically driven - Combination sweeper roller included - Hydraulically driven - Pendulum suspended - 2 height-adjustable wheels via spindles with thrust bearing 200 x 50 mm - Rubber spray flaps - Supports included ABR 50 required KM 14750 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 147 cm KM 16550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm KM 16550 H-ABR 50 (without attachment frame) Sweeper hydraulically driven Working width 165 cm Attachment frame for compact tractor sweepers Working width 165 cm KM 13050 H-ABR 50 DP Attachment frame for dome-triangle mounting ABR 50 KD Attachment frame for dome-triangle mounting ABR 50 KD Attachment frame three-point linkage Cat I and II ABR 50 FM Attachment frame area mower (2-point) | | | Working width 165 cm |
| (without attachment frame)Working width 147 cm For further description see KM 13050 H-ABR 50KM 16550 H-ABR 50 (without attachment frame)Sweeper hydraulically driven Working width 165 cm For further description see KM 13050 H-ABR 50Attachment frame for compact tractor sweepers When ordering, specify exact carrier vehicle type and tachment type.Attachment frame for dome-triangle mountingABR 50 KDAttachment frame for dome-triangle mountingABR 50 DPAttachment frame three-point linkage Cat I and IIABR 50 FMAttachment frame area mower (2-point) | | | Working width 165 cm Hydraulically driven internal orbital motor Quick change axle Combination sweeper roller included Hydraulic left and right swivel (1 x dw required) Pendulum suspended 2 height-adjustable wheels via spindles with thrust bearing 200 x 50 mm Rubber spray flaps Supports included |
| Min rosso in Abrision Working width 165 cm (without attachment frame) For further description see KM 13050 H-ABR 50 Attachment frame for compact tractor sweepers When ordering, specify exact carrier vehicle type and attachment type. ABR 50 KD Attachment frame for dome-triangle mounting ABR 50 DP Attachment frame three-point linkage Cat I and II ABR 50 FM Attachment frame area mower (2-point) | | | Working width 147 cm |
| When ordering, specify exact carrier vehicle type and attachment type. ABR 50 KD Attachment frame for dome-triangle mounting ABR 50 DP Attachment frame three-point linkage Cat I and II ABR 50 FM Attachment frame area mower (2-point) | | | Working width 165 cm |
| ABR 50 DP Attachment frame three-point linkage Cat I and II ABR 50 FM Attachment frame area mower (2-point) | | | |
| ABR 50 FM Attachment frame area mower (2-point) | | ABR 50 KD | Attachment frame for dome-triangle mounting |
| | | ABR 50 DP | Attachment frame three-point linkage Cat I and II |
| | | ABR 50 FM | |

Description

Compatible with sweeper

KM 13050

| Options/Accessories | | |
|--|-------------|-------------------|
| Dirt collection tank Including hydraulic container emptying Container made of sheet steel Plug-in mounted | ltem number | SSB 13050 B |
| Attachment side broom 50 cm • Hydraulically driven • With mounting plate • Separate oil supply for the side broom on the sweeper • Infinitely adjustable via control valve • Separately switchable • Hard disc broom • Suitable for all KM M (mechanical drive) | ltem number | ASH 50 KM 4050 M |
| Attachment side broom 50 cm • Suitable for all KM H (hydraulic drive) For further description see ASH 50KM 4050 M | Item number | ASH 50 KM 4050 H |
| Water sprinkler 100 litres Electric submersible pump 12 V Spray nozzles for even distribution Suitable for three-point attachment KAT 1 12 V plug-in coupling required on carrier vehicle | Item number | WAS 100 KAT 1 |
| Water sprinkler 100 litres Electric submersible pump 12 V Spray nozzles for even distribution Water barrel mounted on the KM 12 V plug-in coupling required on carrier vehicle | Item number | WAS 100 AUF-KM 50 |
| Water sprinkler 200 litres Electric submersible pump 12 V Spray nozzles for even distribution Water barrel in rear three-point linkage 12 V plug-in coupling required on carrier vehicle | Item number | WAS 200 KAT I |
| Running wheels 180 x 80 mm Including heavy turntable, instead of the standard wheels | ltem number | MP-RD 180 X 80 |
| Electromagnetic valve For installation in the sweeper, thus only 1 dw required Function: swivel and sweeper drive | Item number | EMV-KM 50 |
| Supports for sweeping roller diameter 40 or 50 cm With castors For easier mounting and dismounting of the sweeper For storage of the sweeper | ltem number | AST 4050 LR |
| Sprocket For increasing the speed when sweeping snow | ltem number | S1138 |
| Red-white marker lights | ltem number | BGL-KM 50 |
| Set of warning flags with holder | Item number | WA-FLAG-KM 50 |



| KM 14750 | KM 16550 |
|-------------------|-------------------|
| | |
| SSB 14750 B | SSB 16550 B |
| ASH 50 KM 4050 M | ASH 50 KM 4050 M |
| ASH 50 KM 4050 H | ASH 50 KM 4050 H |
| WAS 100 KAT 1 | WAS 100 KAT 1 |
| WAS 100 AUF-KM 50 | WAS 100 AUF-KM 50 |
| WAS 200 KAT I | WAS 200 KAT I |
| MP-RD 180 X 80 | MP-RD 180 X 80 |
| EMV-KM 50 | EMV-KM 50 |
| AST 4050 LR | AST 4050 LR |
| S1138 | S1138 |
| BGL-KM 50 | BGL-KM 50 |
| WA-FLAG-KM 50 | WA-FLAG-KM 50 |